



	DBD14	DBD24TL	DBB33TL-PK4	DBB43TL	DBB44TL	DBB54TL	DEZ06T10
	High Resolution Varifocal Indoor Dome	Ultra Resolution Varifocal Indoor IR Dome	Ultra Resolution Outdoor IR Bullet 4 Pack	Ultra Resolution Outdoor IR Bullet	Ultra Resolution Varifocal Outdoor IR Bullet	Ultra Resolution Varifocal Outdoor IR Bullet	10X PTZ Camera - Mini form factor (3.3" dome diameter)
Image Sensor	1/3" Sony Super HAD™	1/3" Ultra Resolution	1/3" Ultra Resolution	1/3" Ultra Resolution	1/3" Ultra Resolution	1/3" 960H Sony EXview™ II	1/3" Sony Super HAD™ II CCD
TV Line Resolution	540 TVL	600 TVL	600 TVL	600 TVL	600 TVL	700+ TVL, 960H	700+ TVL, 960H
Lens	2.8-10.5mm	2.8-12mm	3.6mm	3.6mm	2.8-12mm	2.8-12mm	Zoom, 3.8-38mm
Voltage Requirement	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC
Night Vision Technology	-	IR - 65 ft	IR - 85 ft	IR - 70 ft	IR - 90 ft	IR - 90 ft	Polaris Vision / TDN
Key Features	<ul style="list-style-type: none"> Detachable camera base for easy installation Wall/ceiling mount 	<ul style="list-style-type: none"> TDN with Mechanical ICR 3 Axis Gimbal Wall/ceiling mount 	<ul style="list-style-type: none"> TDN with Mechanical ICR Cold climate (min -22°F) Anti-glare technology IP66 weatherproof 	<ul style="list-style-type: none"> TDN with Mechanical ICR Cold climate (min -22°F) IP66 weatherproof Cable through bracket 	<ul style="list-style-type: none"> TDN with Mechanical ICR External lens adjustment Cold climate (min -22°F) Cable through bracket, IP66 	<ul style="list-style-type: none"> TDN with Mechanical ICR External lens adjustment IP66 weatherproof Cable through bracket 	<ul style="list-style-type: none"> 10x Optical/10x Digital Zoom Hi-Speed Pan/Tilt 360°/Sec Surface/Flush Mount Support IP66 w/ Included Wall Mount



	DBV43TL	DBV34TL	DBV44TL	DBV54TL
	Ultra Resolution Outdoor IR Vandal Dome	Ultra Resolution Varifocal Vandal Outdoor IR Dome	Ultra Resolution Varifocal Vandal Outdoor IR Dome	Ultra Resolution Varifocal Vandal Outdoor IR Dome
Image Sensor	1/3" Ultra Resolution	1/3" Ultra Resolution	1/3" Ultra Resolution	1/3" 960H Sony EXview™ II
TV Line Resolution	600 TVL	600 TVL	600 TVL	700+ TVL, 960H
Lens	3.6mm	4-9mm	2.8-12mm	2.8-12mm
Voltage Requirement	12V DC	12V DC	12V DC	12V DC
Night Vision Technology	IR - 65 ft	IR - 90 ft	IR - 90 ft	IR - 90 ft
Key Features	<ul style="list-style-type: none"> TDN with Mechanical ICR Cold climate (min -22°F) IP66 weatherproof Wall/ceiling mount 	<ul style="list-style-type: none"> TDN with Mechanical ICR Cold climate (min -22°F) External Zoom/Focus Wall/ceiling mount, IP66 	<ul style="list-style-type: none"> TDN with Mechanical ICR Cold climate (min -22°F) External lens adjustment Wall/ceiling mount, IP66 	<ul style="list-style-type: none"> TDN with Mechanical ICR External lens adjustment IP66 weatherproof Wall/ceiling mount



Summit Feature Highlights

- Ultra Resolution
- Wide Angle Viewing
- IR Night Vision
- 12 V DC operation
- True Day / Night (TDN)
- Wall / ceiling mountable
- IP66 weatherproof rating
- 1 Year Warranty