

DIGIMERGE | Right for Business

Echelon Series - Ultra Resolution Cameras



ECHELON Series



	DCB23DL	DCB34DL	DCB44DL	DCV23DL	DCV24DL	DEZ26TO22
	Ultra Resolution IR Weatherproof Bullet	Ultra Resolution Varifocal Outdoor IR Bullet	Ultra Resolution Varifocal Outdoor IR Bullet	Ultra Resolution IR Vandal Outdoor Dome	Ultra Resolution Varifocal IR Vandal Outdoor Dome	Mini Vandal Outdoor TDN 22x PTZ Dome
Image Sensor	1/3' Sony Super HAD™ II CCD	1/3' Sony Super HAD™ II CCD	1/3' Sony Super HAD™ II CCD	1/3' Sony Super HAD™ II CCD	1/3' Sony Super HAD™ II CCD	1/4' Sony ExView™ CCD
TV Line Resolution	600 TVL	600 TVL	600 TVL	600 TVL	600 TVL	580 TVL
Lens	3.6 mm	2.8 - 12 mm Varifocal	2.8 - 12 mm Varifocal	3.6 mm	2.8 - 12 mm Varifocal	3.9 - 85.8 mm, Zoom
Night Vision Technology	IR - 60 ft	IR - 75 ft	IR - 75 ft	IR - 50 ft	IR - 66 ft	Polaris Vision, TDN
Voltage Requirement	12V DC	12V DC	12V DC / 24V AC	12V DC	12V DC / 24V AC	12V DC / 24V AC
Key Features	<ul style="list-style-type: none"> Advanced DNR Wall/ceiling mount IP66 Weatherproof 	<ul style="list-style-type: none"> Advanced DNR External Zoom/Focus adjustment Cable through bracket IP66 Weatherproof 	<ul style="list-style-type: none"> Advanced DNR External Zoom/Focus adjustment Cable through bracket IP66 Weatherproof 	<ul style="list-style-type: none"> Advanced DNR Wall/ceiling mount IP67 Weatherproof 	<ul style="list-style-type: none"> Advanced DNR External Zoom/Focus adjustment Wall/ceiling mount IP66 Weatherproof 	<ul style="list-style-type: none"> Day/Night mode with ICR 22X optical zoom / 16X digital Pan: 360° Endless, Tilt: 0° ~ 180° Max Pan/Tilt Speed 380°/sec RS485 control / IP66

Also Available: ECO Series



DBD13 / DBD13-PK4



DBD14

	DBD13	DBD13-PK4	DBD14	DEZ26TO22
	Single High Resolution 3 Axis Dome	High Resolution 3 Axis Dome 4 Pack	High Resolution 3 Axis Varifocal Dome	High Resolution Outdoor IR Bullet 4 Pack
Image Sensor	1/4" High Res.	1/4" High Res.	1/3" Sony Super HAD™	1/4" High Res.
TV Line Resolution	480 TVL	480 TVL	540 TVL	480 TVL
Lens	3.6 mm	3.6 mm	2.8-10.5 mm	5.1 mm Pure Flat
Key Features	<ul style="list-style-type: none"> Color rolling suppression Anti-glare technology Wall/ceiling mount 	<ul style="list-style-type: none"> Color rolling suppression Anti-glare technology Wall/ceiling mount 	<ul style="list-style-type: none"> Wide range varifocal lens Detachable camera base for easy installation Wall/ceiling mount 	<ul style="list-style-type: none"> TDN with Mechanical ICR Color Rolling Suppression Anti-glare technology 50 ft IR Night Vision / IP66



DEZ26TO22

WWW.DIGIMERGE.COM

Echelon Feature Highlights

- Ultra Resolution - 600 TVL
- Wide Angle Viewing
- IR Night Vision
- 12 V DC / 24V AC operation
- Advanced Digital Noise Reduction (DNR)
- Wall / ceiling mountable
- IP66 weatherproof rating
- 3 Year Warranty

ECHELON Series

E&OE. Specifications and camera design are subject to change.